



## SPECIFICATIONS

		SINGLE UNITS							SWITCHABLE UNITS					
FILTER MODEL	MEASUREMENT	SEPAR 2000 /5	SEPAR 2000 /5/50	SEPAR 2000 /10	SEPAR 2000 /18	SEPAR 2000 /40	SEPAR 2000 /40/2MK	SEPAR 2000 /130	SEPAR 2000 /5U	SEPAR 2000 /5/50U	SEPAR 2000 /10U	SEPAR 2000 /18U	SEPAR 2000 /40U	SEPAR 2000 /130U
MAX FLOW	GPH	79	79	158	285	634	1268	2060	79	79	158	285	634	2060
	LPH	300	300	600	1080	2400	4800	7800	300	300	600	1080	2400	7800
FILTER RESTRICTION at Max Flow 30 Mic Element	IN.HG	.59	.53	.31	.44	.95	.95	.95	.59	.53	.31	.44	.95	.95
	MBAR	20	18	11	15	32	32	22	20	18	11	15	32	22
PORT SIZE	INCHES	3/4 -16	3/4 -16	7/8 -14	1 1/8 -12	1 5/16 -12	2" PIPE	2" PIPE	7/8 -14	7/8 -14	11/16 -12	15/16 -14	1 7/8 -12	2" PIPE
	METRIC	16x1.5	16.1.5	22x1.5	26x1.5	33x2			12mm	12mm	15mm	22mm	35mm	
HEIGHT	INCHES	10.15	11.54	13	15.15	19	19	32	11.75	13.11	15	18	20.87	32
	MM	258	293	328	385	480	480	813	298	333	378	453	530	813
ELEMENT REMOVAL	INCHES	1.5	3	3	3	3	3	3	1.5	3	3	3	3	3
	MM	30	60	60	60	60	60	60	30	60	60	60	60	60
TOTAL HEIGHT NEEDED	INCHES	12	14	16	18	22	22	35	11.75	14	16	18	22	35
	MM	304	356	406	457	559	559	889	298	356	406	457	559	889
DEPTH	INCHES	3.66	3.66	4.21	6.5	8.3	8.3	14.6	6.3	6.3	7.6	9	11	19
	MM	93	93	107	165	211	211	370	160	160	194	226	280	480
WIDTH	INCHES	5.5	5.5	5.75	8	11.5	34	18.2	17.32	17.32	18	24.6	31.3	46.3
	MM	140	140	146	200	290	863	460	440	440	460	625	795	1175
WEIGHT	LBS.	3	4	5	11	24	69	99	10	11	18	42	81	237
	KG.	1.4	1.8	2.3	5	11	31	45	4.5	5	8.2	19	37	108